

Care and cleaning EUROFLEX Impact Protection Slabs

EUROFLEX Impact Protection slabs are nearly maintenance-free unlike loosely poured sand or park mulch.

Regular cleaning of your installed EUROFLEX surface will promote a long useful life as well as attractive appearance.

Impurities can be cleaned with a soft-bristled broom or vacuuming with an industrial vacuum cleaner.

If moss and algae to result from atmospheric exposure, is recommended to use a high pressure water cleaner until 200bar without chemical additives!

Attention! The water pressure must be not too high.

The distance of water jet to the surface area should be minimum 30cm and the water temperature not higher than 80°C.

This cleaning of surface is to be made one time yearly.

Adherent impurities can be excluded with water and a scrubber.

It is possible to use a dilution soap suds.

After cleaning is recommended use water as a chaser.


If it is necessary removal snow at winter, keep in mind that the coating not breaks down by sharp-edged or to be overweight machinery or implements.

The application with commercial, allowed de-icing salt won't hurt the coating.

Attention! Don't use solvent based cleansing material.

They can damage the coating.

EUROFLEX Impact Protection Slabs are an economical solution for any application due to their extreme durability and ease of maintenance.



All information without guarantee, subject to change. The Data Sheet is not subject to any change service.
Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex

page 1 of 2

Sand will be removed at the slabs completely.



The result was perfect.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.
Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex